7251/7351 Slice

Durable construction, dependable performance Flexible pad-mount or post-mount with

Flexible pad-mount or post-mount with superior solar performance and an array of installation configurations.

Features:



Powerful: Move gates up to 800 lbs and 25 ft long.



Low maintenance: Easy to install and maintain.



Convenience: Designed for easy access to limit switch adjustment.



Battery: 12VDC battery powered.





Flexible:

AC or Solar power options.



Performance:

Durable components provide weather operation.



Technology:

Nice BlueBUS 2-wire system self-identifies monitored photo eyes.



Made in USA: Designed, tested and built within USA from globally sourced materials.

7251/7351 Slide Residential, Farm, Ranch Applications





Technical Specifications

| Model | Apollo 7251 Slide | Apollo 7351 Slide |
|----------------------|---|---|
| Operator Kit | 7251 - Post Mount | 7351 - Pad Mount |
| Duty Cycle | Varies based on charging capacity* | |
| Drive | Electromechanical | |
| Rate of Travel | 1 ft/sec (30 cm/s) | |
| Gate Length Max. | 25 ft (7 m) | |
| Gate Weight Max. | 800 lb (362 kg) | |
| Temperature Rating | -4° to 122° F (-20° to 50° C) | |
| Operating Voltage | 12VDC | |
| Input Voltage | 12VDC or 24VDC | |
| Idle Current | 17mA | |
| Accessory Power | 12VDC and 24VDC 0.3A each location | |
| Included Accessories | OXIBD bi-directional receiver, one set of BlueBUS through beam photo eyes | |
| Communication | BlueBUS, BUST4, USB port, OXI | |
| User Controls | 1050 Controller | |
| Relays | 3 programmable | |
| Enclosure | 22w x 22h x 15.5d inch (56w x 56h x 39.4d cm) | 20.5w x 26.5h x 18d inch (52w x 67.3h x 45.7d cm) |
| Control Box Finish | Powder coated black steel | |
| ETL Listed (UL 325) | Usage Class I, II | |
| Warranty | 3 year w/product registration | |
| | | |

* Actual battery backed up cycles will depend on gate resistance to travel, cycle length, battery health, ambient temperature, accessory power draw and frequency of gate cycles during power outage.

Note: Battery and battery charger or solar panel required for operation, not included.





support.hysecurity.com

Nice

Nice/HySecurity is an industry leader of automated gate and perimeter security solutions.

The HySecurity brand provides high-quality, ultra-reliable industrial gate operators and crash-rated, Hostile Vehicle Mitigation (HVM) vehicle barriers designed to secure and protect critical infrastructure and facilities worldwide.

Niceforyou.com

©2023 Nice North America LLC. HySecurity is a registered trademark of Nice North America LLC. All rights reserved. All trademarks, logos and brand names are the property of their respective owners.