

Features:



Battery:

24VDC operator.



Design:

Arm lengths from 8 to 29 ft.



Reliable:

Available battery backup maintains operations in case of power outage.



Efficient:

Automatically switches to standby mode when idle to reduce consumption and save energy.



Swift:

Smooth, graceful movement through full cycle using motion control technology for long service life.



Visible:

Optional integrated flashing or traffic light.



Intelligent:

Obstacle detection reverses arm on contact.



Gate types:

Dual gate pairing through primary/ secondary communication.



Applications:

Solar option available.



M-Bar/L-Bar

Traffic/Road Access Control





Technical Specifications

| Model | Nice M3BAR | Nice M5BAR | Nice M7BAR | Nice L9BAR |
|---------------------|--|----------------------------------|-----------------------------------|-----------------------------------|
| Arm Length Max. | 8 to 10 ft (2.4 to 3 m) | 10 to 16 ft (3 to 5 m) | 16 to 23 ft (5 to 7 m) | 23 to 29 ft (7 to 8.9 m) |
| Arm Design | Aluminum arm with red adhesive reflector and optional lights/bumper strips | | | |
| Full Open Angle | Adjustable to 90° (recommended to limit at 87°) | | | |
| Duty Cycle | 500 cycles/hr | 350 cycles/hr | 200 cycles/hr | 150 cycles/hr |
| Drive | Electromechanical | | | |
| Open/Close Time | 1.5 - 4 seconds. Field adjustable. | 3 - 6 seconds. Field adjustable. | 6 - 10 seconds. Field adjustable. | 8 - 10 seconds. Field adjustable. |
| Ingress Protection | IP44 | | | |
| Handing | Universal: field adaptable for left hand or right hand installations | | | |
| Temperature Rating | -4° to 122° F (-20° to 50° C) | | | |
| Operating Voltage | 24VDC | | | |
| Input Voltage | 120VAC 60/50Hz | | | |
| Accessory Power | 24VDC | | | |
| Communication | Optional Oview programmer, OVBT | | | |
| User Controls | BCU1 Control Board | | | |
| Relays | 4 programmable voltage outputs | | | |
| Finish | Cataphoretic coating and paint finish | | | |
| ETL Listed (UL 325) | Usage Class I, II, III, IV | | | |
| Cycle Tested | 1 million cycles | | | |
| Warranty | 3 year w/product registration | | | |





support.hysecurity.com

Nice/HySecurity is an industry leader of automated gate and perimeter security solutions.

The HySecurity brand provides high-quality, ultra-reliable industrial gate operators and crash-rated, Hostile Vehicle Mitigation (HVM) vehicle barriers designed to secure and protect critical infrastructure and facilities worldwide.



Niceforyou.com