

## HydraWedge™ SM50 Order Form

To process your HydraWedge™ SM50 order, it is a HySecurity requirement that you fill out all the customer information fields on this Order Form and sign all the necessary applications and agreements.

**A separate order form is required for each unique operator ordered.** If you have multiple identical operators, with NO variances, indicate total quantity here: \_\_\_\_\_

Date: \_\_\_\_\_ Purchase Order #: \_\_\_\_\_

Installer Company: \_\_\_\_\_ Contact Person Name: \_\_\_\_\_

Contact Phone #: \_\_\_\_\_ Contact Email: \_\_\_\_\_

Job site: \_\_\_\_\_ Job site City, State: \_\_\_\_\_

**INSTRUCTIONS: Check one box within each of the numbered sections below. The order form must be fully completed and signed before the order will be processed.**

### 1) Model:

- HydraWedge SM50
- HydraWedge SM50 Twin (Wedges operate with two independent controls and one HydraSupply XL™)
- HydraWedge SM50 UPS
- HydraWedge SM50 Twin UPS (Wedges operate with two independent controls and one HydraSupply XL™)

### 2) Voltage and Phase: (Check one)

**Standard AC model, HydraWedge:** AC Supply Voltage



**60HZ:**  208 V 1Ø  230 V 1Ø  208 V 3Ø  230 V 3Ø  460 V 3Ø  575 V 3Ø 

**50HZ:**   220 V 1Ø  220 V 3Ø  380 V 3Ø  440 V 3Ø

**UPS Backup model, 24 VDC, HydraWedge UPS:** AC Input Voltage for UPS Backup. AC Input Voltage for UPS Backup. Choose voltage with care as chargers are not field convertible. \*115V requires a 30A branch circuit

115 V 1Ø, 23A  208 - 230 V 1Ø, 11.5A

### 3) Accumulator size (Check one)


- 2.5 gallon: 6 cycles 
- 5 gallon: 12 cycles  (not available for Twin model)

### 4) Plate width: (Check one)

Base frame is W x L x H: (Plate width + 7.8 inch) x 6.4 x 1 ft (plate width + 24 x 195 x 30 cm)

- 2 m (6.5 ft)
- 2.5 m (8 ft)
- 3 m (10 ft)
- 3.5 m (11.5 ft)
- 4 m (13 ft)

 - Indicates an additional charge. See Price Book for details.

**6) Options:**  Consult HySecurity for lead time at time of order. (Check all that apply)

- |  |  |  |   |  |
|--|--|--|---|--|
| <input type="checkbox"/> 460V Heater                           | <input type="checkbox"/> Red LED light strip                                       |  |   |  |
| <input type="checkbox"/> Biodegradable Fluid                   | <input type="checkbox"/> Custom color, blocking element (complete assembly): _____ |  |   |  |
| <input type="checkbox"/> Radio Receiver: Single Channel Open** | <input type="checkbox"/> Custom color, cover plate (top of the plate): _____       |  |   |  |
| <input type="checkbox"/> Skirt:                                | <input type="checkbox"/> Flame Red   | <input type="checkbox"/> Flame red, pure white cross striped | <input type="checkbox"/> Jet black, daffodil yellow cross striped | <input type="checkbox"/> Other RAL color |

\*\*\* Note: Installing a wired transmitter requires a separate run of conduit for low voltage wires

**Hoses:**

Hoses are ordered on a separate order form. In most installations, the hose order is placed after the operator is installed to ensure that hose lengths are accurate.

Operator price includes up to 50 ft (15 m), (150 ft (45.7 m) for twin models), of 3/8 inch hydraulic hose (custom cut to size by HySecurity according to installer's field measurements). Hoses are pre-filled with hydraulic fluid and supplied with quick disconnects. Submit completed and signed operator and hose order forms with each order. **HySecurity will invoice for any hose over the included length of hose.**

**Double check that one box within each of the numbered sections above has been checked. The Order Form must be fully completed and signed before the order will be processed.**

**It is the responsibility of the HySecurity Distributor/Dealer to verify that the information on this order form is accurate. As stated in the Global Sales Agreement, custom orders are non-returnable.**

**Order has been reviewed and approved by:**

\_\_\_\_\_  
PRINT NAME

\_\_\_\_\_  
HYSECURITY DISTRIBUTOR/DEALER

\_\_\_\_\_  
SIGNATURE

\_\_\_\_\_  
DATE

**FOR INTERNAL USE ONLY**

**Prior to processing the order, all of the following requirements must be met:**

**Dealer Requirements:**

- Fortified Crash Barrier Dealer Application
- Fortified Crash Barrier Dealer Credit Application
- Global Sales Agreement
- Maintains \$2 million of liability insurance coverage and a security bond of \$50,000 minimum
- Certificate of Attendance: HySecurity Tech Training
- Certificate of Attendance: HySecurity Fortified Crash Barrier Technical Installation Training
- OR  HySecurity On-Site Training for First Installation Agreement

\_\_\_\_\_  
SIGNATURE

\_\_\_\_\_  
DATE