

Swing for the Fences

11 models: 600 to 15,000 lb.


Choose the perfect LA swing gate operator




5 Models



6 Models



4 Models



2 Models

Rural | Solar | Residential | Utility | Estate | High Security





16 ft Max



Nice **1500/1551**

Farm/ranch and Residential



1551 LA System: 1050 Control Board, CBOX, 816 arm

- Move up to 600 lb/16 ft gate leaf
- Perfect for AC or Solar applications*
- Single or dual gate applications
- Easy to install and low maintenance
- Proven reliability and durability. More than 100,000 installations
- Corrosion resistant acme screw drive mechanism
- All weather performance
- 2 year warranty

* Battery required for operation, not included

1500 LA System
Farm/Ranch Only
636 control board
16 ft leaf (5 m) 600 lb
leaf (272 kg)
14-16 second open

1551 LA System
1050 control board
16 ft leaf (5 m) 600 lb
leaf (272 kg)
14-16 second open

Bundle 310 AC
310 control board
600 lb/20 ft leaf (272
kg/6m)
1000 lb/8ft leaf
(453/2.4 m)
14-16 second open




20 ft Max



Nice **TITAN12L/12L1**

Residential



TITAN12L1 LA System: 1050US Board, CBOX, 912L-1 arm

- Move up to 600 lb/20 ft gate leaf or 1,000 lb/8 ft gate leaf
- Perfect for AC or Solar applications*
- Single or dual gate applications
- Convenient access to limit switch adjustment, secured under locking cover
- Keyed release for manual operation
- Engineered for quiet operation and smooth start and stop control
- Superior arm design keeps out dust and snow
- Compatible with mounting geometry of Nice 1500 series actuators
- 2 year warranty

* Battery required for operation, included

TITAN12L1 LA System
Residential
1050 control board
600 lb/20 ft leaf (272 kg/6 m)
1000 lb/8 ft leaf (453/2.4 m)
14-16 second open

TITAN Bundle 310 Solar
Residential, Farm/Ranch
SolarBOX310/Mercury 310/
TITAN 912L
600 lb/20 ft leaf (272 kg/6 m)
1000 lb/8 ft leaf (453/2.4 m)
14-16 second open



24 ft Max

HydraSwing 40/40F

Industrial and High Security



HydraSwing 40, 40F: Smart Touch Board, HydraSupply

- Recommended for swing gates subject to extreme peak winds
- Move large, heavy gates up to 4,000 lb/24 ft
- Sturdy zinc plated 1/4 inch steel chassis with stainless steel cover
- Industrial grade components for extremely low maintenance and exceptionally long life
- Dual gate, sally port or sequenced gate integration
- Easy system troubleshooting with onboard event log
- UPS backup with optional AC Power Supply w/HyInverter AC™
- 5 year warranty

HydraSwing 40/Twin
Industrial and high security
 4,000 lb (1,814 kg) leaf
 up to 24 ft (7.3 m) leaf
 Twin: up to 16 ft (5 m) leaf
 15-20 second open


HydraSwing 40F/Twin
Industrial and high security
 4,000 lb (1,814 kg) leaf
 up to 16 ft (5 m) each leaf
 10-15 second open



40 ft Max

HydraSwing 80F/150

Industrial and High Security



HydraSwing 80F, 150: Smart Touch Board, HydraSupply

- Recommended for swing gates subject to extreme peak winds
- Move large, heavy gates up to 15,000 lb/40 ft
- Extra robust 3/4 inch zinc plated steel chassis with black powder coated steel cover.
- Industrial grade components for extremely low maintenance and exceptionally long life
- Dual gate, sally port or sequenced gate integration
- Easy system troubleshooting with onboard event log
- UPS backup with optional AC Power Supply w/HyInverter AC™
- 5 year warranty

HydraSwing 80F
 8,000 lb (3,629 kg) leaf
 up to 30 ft (9 m) leaf
 15-25 second open

HydraSwing 150
 15,000 lb (6,804 kg) leaf
 up to 40 ft (12 m) leaf
 20-30 second open

Linear Actuators for all applications

CONTROL BOARD FEATURES

Nice 636US CONTROLLER APOLLO 1550 LA SYSTEM	Nice 1050 CONTROLLER APOLLO 115 LA SYSTEM TITAN12L1 SYSTEM	Nice MERCURY 310 CONTROLLER APOLLO BUNDLE 310 TITAN BUNDLE 310	SMART TOUCH CONTROLLER HYDRASWING 40, 40F, 40 TWIN, 80F, 150
Excellent for solar applications	Built-in solar regulator and charger	12/2A with MPP	Patent Anti-Tailgate mode
Simple to install and configure	Simple to install and configure	Simple to install and configure	Ample user inputs
Single or dual gate	Single or dual gate	Dual gate synchronization	Solid state and SPDT installer configurable relay outputs for many interface options
Compatible with N/O (unmonitored) photo eyes	Compatible with Vanguard 3501, TITAN, Apollo	Supports up to 1,000 Inti or Era One remotes with rolling-code security	Optional plug-in Hy5B vehicle detectors.
Not UL 325 Certified	BlueBUS and 10K monitored sensors; pulsed photo eyes	BlueBUS, USB port, OXI, 433MHz remote	USB and RS-232 for connection to laptop
	Smart battery charging management	Prominent Battery Health LED warns of potential battery problems	Dual gate, sally port or sequenced gate integration
	Simple retrofit of 600 and 800 series board	Full-featured controller with over 100 option settings	RS-232, RS-485
	For linear actuator applications only	Digital display for detailed user feedback	Configurable "warn before operate" buzzer
	UL 325 Usage Class I, II, UL 991	Surge protection	Configurable operator with keypad, or laptop computer using S.T.A.R.T. software
		Built in solar regulator and charger	Power surge/lighting strike protection
		"Fire" input for emergency access devices	Battery protection software prevents over-discharge-lengthens battery life
		UL 325 Class I, II	UL 325 Class I, II, III, IV

Optional Accessories (Excluded 636US Controller)



Optional Accessories (HydraSwing)



HySecurity
a Nice company
support.hysecurity.com

Nice/HySecurity is an industry leader of automated gate and perimeter security solutions.
The HySecurity brand provides high-quality, ultra-reliable industrial gate operators and crash-rated, Hostile Vehicle Mitigation (HVM) vehicle barriers designed to secure and protect critical infrastructure and facilities worldwide.

Nice
Niceforyou.com
©2023 Nice North America LLC. All rights reserved.
HySecurity is a registered trademark of Nice North America LLC.
All trademarks, logos and brand names are the property of their respective owners.