

## StrongSlide<sup>™</sup> HVM Gate

## Quote Request and Order Form

Dat	е	Person Completing form								
Dea	aler	Ship-to Contact name								
Dis	tributor	Ship-to Contact phone								
Purchase Order # Job Name			Job City	State						
1.	Qty	Only one form is required when ord	ering multiple, identical Stron	gSlide gates.						
2.	Model	StrongSlide M30	StrongSlide M50							
		↓ IMPACT ↓ DIRECTION ↓								
	-	CLEAR OPEN								
				- SLIDEDRIVER II GATE OPERATOR						
				FRAME TOP GUIDE TRACK  DRIVER RAIL  GATE SUPPORT POST  HEIGHT  GRADE						
3.	GATE HANDING (Illustration above is Right Handed)									
		Right Handed	Left handed	TBD (Quotes only)						
		Gate opens to the right when viewed from the secure side	Gate opens to the left when viewed from the secure side							
4.	GATE DIMENSI	IONS	ı	I						
	ft Clear Opening: (12-24 ft. This is not the gate length, but the needed clearance for vehicle traffic. HySecurity will use this information to determine the gate length. Round up to the nearest whole ft.)									
		t: (This is the height of the top rail of the top to the nearest whole ft. 7ft minimun		ng the length of pickets or barb wire arms.						

5. GATE FINISH										
Galvanized (G90 or better)				Powder coat						
POWDER C	COAT COLOR (C	Circle one)								
Patrician Bronze	Desert Sand	Canyon Brown	Cinder Black	Bronze	Polar White	Stardust Silver	Other: RAL			
6. CATCH	BOLLARD FINIS	Н								
7. <b>INFILL</b>	Galvanized			Powder co	pat	Powder coat colo				
	Field Installed			Factory Installed						
	Infill type Describe, including manufacturer name and fence type			Top edge enhancement Describe, including barb wire arms, shark teeth, etc.						
Estimate weight of infill (lbs/sq. ft.)										
	Ship in adv	ance	curity will ship	these elements	in advance to	prepare the site fo	r gate installation.			
	a Nice brand	The HySec Hostile Veh	urity brand pro	vides high-quality	, ultra-reliable	e industrial gate oper	er security solutions. ators and crash-rated, ect critical infrastructure			



Niceforyou.com