



**AC POWER IN**  
FOR SINGLE PHASE (1Ø)  
CONNECT TO L1 & L3  
FOR 3Ø  
CONNECT TO L1,L2 & L3

**A 20A CIRCUIT BREAKER MUST BE PROVIDED IN THE FIELD BY THE INSTALLER**

UNLESS OTHERWISE SPECIFIED,  
DIMENSIONS ARE INCHES.  
TOLERANCES IN DECIMAL:  
2 PLS (0.XX) = ± .03  
3 PLS (0.XXX) = ± .005  
ANGLES = ± 0.5  
**DO NOT SCALE DRAWING**

**HySecurity**  
Simple. Reliable. Secure.  
Hy-Security Gate, Inc. 6623 South 228th St. Kent, WA 98032-1876  
PROPRIETARY INFORMATION OF HY-SECURITY GATE, INC.  
This document, and the information contained herein, are the confidential, proprietary and trade secret information of Hy-Security Gate, Inc. (Hy-Security). Any party receiving, accepting or retaining this document thereby agrees to use the document, and any information contained therein, solely as may be required to manufacture products or components for Hy-Security and will not provide this document or any information therein to any other party, or use it for any other purpose, without the express, prior, written consent of Hy-Security.

NAME	DATE	DESCRIPTION:
DRAWN RAW	4/4/2017	WIRING DIAGRAM, M200 VFD, SD
CHECKED		
ENG APPR.		PART NO.:

REV BY	REV DATE	FINISH: N/A	WEIGHT:	LBS	SHEET 1 OF 1
RAW	4/4/2017				

ECN NO.	REV	CHANGE DESCRIPTION
N/A	A	INITIAL RELEASE FOR ENGINEERING