


UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE INCHES.
TOLERANCES IN DECIMAL:
2 PLS (0.XX) = ± .03
3 PLS (0.XXX) = ± .005
ANGLES = ± 0.5

DO NOT SCALE DRAWING


 Simple. Reliable. Secure.
 Hy-Security Gate, Inc. 6623 South 228th St. Kent, WA 98032-1876
PROPRIETARY INFORMATION OF HY-SECURITY GATE, INC.
This document, and the information contained herein, are the confidential, proprietary and trade secret information of Hy-Security Gate, Inc. (Hy-Security). Any party receiving, accepting or retaining this document thereby agrees to use the document, and any information contained therein, solely as may be required to manufacture products or components for Hy-Security and will not provide this document or any information therein to any other party, or use it for any other purpose, without the express, prior, written consent of Hy-Security.

NAME	DATE	DESCRIPTION: WIRING DIAGRAM, HYDRASUPPLY XL, DOUBLE ACTING AC	PART NO.: D0773 DOUBLE ACTING	MATERIAL: N/A		
DRAWN	RAW 5/10/2016					
CHECKED						
ENG APPR.						
REV BY	RAW	REV DATE	7/5/2018	FINISH: N/A	WEIGHT: LBS	SHEET 1 OF 1

ECN NO.	N/A	REV	B	CHANGE DESCRIPTION	UPDATED TO INCLUDE MX4222 MX4221 PER ENGINEERING REQUEST.
---------	-----	-----	----------	--------------------	---