



UNLESS OTHERWISE SPECIFIED,  
DIMENSIONS ARE INCHES.  
TOLERANCES IN DECIMAL:  
2 PLS (0.XX) = ± .03  
3 PLS (0.XXX) = ± .005  
ANGLES = ± 0.5

**DO NOT SCALE DRAWING**

**HySecurity**  
Simple. Reliable. Secure.  
Hy-Security Gate, Inc. 6623 South 228th St. Kent, WA 98032-1876  
PROPRIETARY INFORMATION OF HY-SECURITY GATE, INC.  
This document, and the information contained herein, are the confidential, proprietary and trade secret information of Hy-Security Gate, Inc. (Hy-Security). Any party receiving, accepting or retaining this document hereby agrees to use the document, and any information contained therein, solely as may be required to manufacture products or components for Hy-Security and will not provide this document or any information therein to any other party, or use it for any other purpose, without the express, prior, written consent of Hy-Security.

NAME	DATE	DESCRIPTION:
DRAWN: RAW	5/10/2016	<b>WIRING DIAGRAM, HYDRASUPPLY XL, DC SINGLE</b>
CHECKED:		PART NO.: <b>D0773_DC_SINGLE</b>
ENG APPR.:		MATERIAL: N/A
REV BY: RAW	REV DATE: 7/5/2018	FINISH: N/A
		WEIGHT: LBS SHEET 1 OF 1

ECN NO. N/A	REV <b>C</b>	CHANGE DESCRIPTION UPDATED TO INCLUDE MX4222 MX4221 PER ENGINEERING REQUEST.
-------------	--------------	---