


1050

High-end residential controller with advanced functionality

Compatible with all Nice residential swing and slide gate operators.



Features:



Configurable

Full-featured controller with more than 100 option settings.




Customizable:

7-day programmable timer.



Smooth operation:

Adjustable soft open/close points.



Solar ready:

Built-in solar regulator and charger.



Compatible:

Uses the full line of Nice BlueBUS and OXI accessories

1050 Controller

For use with residential linear actuators, swing and slide gate operators



Operators



Apollo Linear Actuator



TITAN Linear Actuator



Vanguard 3501 Swing



7251/7351 Slide

Technical Specifications

Model	1050US
Solar	Yes, 12V / 1A with MPP
Single or Dual Gate	Single or dual
Gate Sync	Yes
Slide Compatible	7251 / 7351
Swing Compatible	Vanguard 3501, TITAN, Apollo
Temperature Rating	-4 F to 122 F (-20 C to 50 C)
Input Voltage	12 VDC
Operating Voltage	12 or 24 VDC
Maximum Current	17A
Standby Current	17mA
Accessory Power	12V/24V 300mA each location
BlueBUS	Yes
Board Dimensions	9w x 9h x 2.25d inches
Communciation	BlueBUS, BUST4, OXI, 433MHz remote
User Controls	LCD with menu structure
Inputs	Remote, Open, Close, Stop, Fire
Relays	2 non-programmable
ETL Listed (UL 325)	Usage Class I, II; UL 991
External Entrapment Sensor Options	BlueBUS and 10K monitored sensors; pulsed photo eyes
Important Notes	3 year warranty with product registration

Control Boxes



CBOX

with 1050 Controller

Ideal for Solar Installations

18w x 18h x 8d inch



MB1050

with 1050 Controller

Ideal for AC Installations

14.25w x 15.125h x 9d inch

Find information on Federal Income Tax Residential Solar Credit here:
<https://support.hysecurity.com/hc/en-us/articles/4411636518807-Residential-Solar-Tax-Credit>



Contact Nice for an operator/parts distributor near you.
 phone 253-867-3700 | 800-321-9947
hysecurity.com | sales@hysecurity.com



PN: 948109606 | D1061 101122